

TECHNICAL DATA SHEET

Product Name: Trevista 80 Smooth

<u>Product Specifications</u>	Length x Width x Height	Length x Width x Height	Length x Width x Height
Dimensions Metric (mm):	495 x 330 x 80	330 x 330 x 80	165 x 330 x 80
Dimensions Imperial (inches):	19.5 x 13 x 2	13 x 13 x 2	6.5 x 13 x 2
Individual Weight Kg:	27.86	20.03	9.85
Individual Weight lbs:	61.42	44.15	21.71
Pieces per Bundle	16	32	32
Units per Layer	2	4	4
Bundle Weight Kg	1395.85		
Bundle Weight Lbs	3077.00		

Product Uses:

Residential	Commerical				Other		
Pedestrian	Vehicular	Pedestrian only	Pedestrian & Vehicular	Vehicular Traffic	Accessibility	Slab on Pedestal Set	Permeable
☒	☒		☒				

Physical Parameters

Dimensional tolerances:

Length: -1.0 to +2.0mm

Width: -1.0 to +2.0mm

Height: -3.0 to +3.0mm

Compressive Strength: 50 MPa (min)

Freeze thaw: A maximum of 225g/m² loss of mass after 28 cycles of freezing and thawing or
A maximum of 500g/m² loss of mass after 49 cycles of freezing and thawing

Wet DCOF: 0.85

(Dynamic Co-efficient of Friction)

Colours	Autumn Hill	Carrara	Glacier Creek	Grey Mix	Sandstone Taupe
SRI Values	38	30	34	23	

Notes:

1. Meets and exceeds the requirements of the CSA A231.2:19 Precast concrete pavers and patio slabs.
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.

Please contact your Sales Representative for further product information